

PHOTOMETRIC TEST REPORT

MONET 250 PHASE

astro

MONET 250 PHASE


LIGHT EFFICIENCY:




LIGHT QUALITY:



COLOR TEMPERATURE:




OUTPUT: 394 lm
PEAK: 403 cd
POWER: 9.2 W
PF: 0.82




Tracking number: [n/a](#)

Product name:
Monet 250 Phase
Item number:
1517003
Date and time:
08/05/2026 17:00:41
Description:
IP20 LED Picture Light




CIE 1931
x: 0.455
y: 0.410



SPECTRA



POWER





COLOR DETAILS



TM30: 95.8

CRI: 95.7 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.4	96.8	98.4	93.0	93.6	93.0	99.0	97.7	95.8	93.6	88.8	89.3	94.6	98.1	96.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
97.5	96.5	94.9	95.6	97.2	96.3	95.9	95.2	95.8	95.2	94.9	91.7	93.7	95.6	96.6	97.0

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
95.9	95.5	93.6	92.1	93.6	95.9	95.0	94.1	94.5	93.7	93.2	93.1	94.3	96.1	96.0

CQS: 94.2



COLOR PARAMETERS

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2763 K	95.7	95.8	95.8	100.5	94.2	0.455	0.410	0.260	0.351	0.0000







Rf 95.8

Fidelity index R_f


Rg 100.5

Gammut index Rg

		Graphic shifts (%)	
Hue Bin	R _f	Chroma	Hue
1	97	1%	0%
2	97	1%	-1%
3	95	0%	-3%
4	96	-1%	-3%
5	97	-2%	0%
6	96	0%	2%
7	96	0%	3%
8	95	3%	1%
9	96	2%	0%
10	95	2%	-2%
11	95	2%	-3%
12	92	1%	-5%
13	94	-1%	-5%
14	96	-1%	-3%
15	97	-1%	0%
16	97	0%	-1%



BEAM DETAILS



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
50lx	13lx	6lx	3lx	2lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
4.7fcd	1.2fcd	0.5fcd	0.3fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
50.3	60.2	54.3	49.7	45.3	40.1	33.0	18.6	10.8	9.0	6.5	4.5	3.2	2.2	1.4	0.7	0.3	0.1	0.0	0.0
100%	120%	108%	99%	90%	80%	66%	37%	21%	18%	13%	9%	6%	4%	3%	1%	1%	0%	0%	0%

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
50.3	45.5	46.0	46.5	46.9	47.2	47.2	46.9	46.4	45.3	43.3	40.2	34.9	28.8	24.3	22.2	20.5	18.5	16.3	13.9
100%	91%	91%	92%	93%	94%	94%	93%	92%	90%	86%	80%	69%	57%	48%	44%	41%	37%	32%	28%

Intensities in 180° c-plane


0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
50	79	92	107	124	146	170	195	219	242	265	288	309	327	342	357	371	383	392	398
100%	157%	183%	213%	248%	290%	338%	388%	436%	482%	528%	573%	615%	650%	680%	710%	738%	762%	780%	791%

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°
50.3	45.5	46.0	46.5	46.9	47.2	47.2	46.9	46.4	45.3	43.3	40.2	34.9	28.8	24.3	22.2	20.5	18.5	16.3	13.9
100%	91%	91%	92%	93%	94%	94%	93%	92%	90%	86%	80%	69%	57%	48%	44%	41%	37%	32%	28%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
50.1°	91.5°	111°	76.6%	44.8%

ISO CANDELA DIAGRAM




10%	5 cd
20%	10 cd
30%	15 cd
40%	20 cd
50%	25 cd
60%	30 cd
70%	35 cd
80%	40 cd
90%	45 cd

Conditions:

Number of c-planes: 72

Candela at center: 50 cd

ISO LUX DIAGRAM



3%	15.1m lx
5%	25.1m lx
10%	50.3m lx
30%	0.151 lx
50%	0.251 lx

Conditions:

Number of c-planes: 72

Lux at center: 0.503 lx

Lux distribution on a surface
when lamp is mounted at 10
meters from the surface.

GLARE EVALUATION ACCORDING TO UGR


UGR data could not be calculated due to missing/wrong symmetry. Go to Edit -> Photometric -> Corrections and select Correct asymmetry (UGR not defined for asymmetrical distributions)..

COEFFICIENTS OF UTILIZATION

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	101	101	101	99
1	108	103	98	94	105	100	96	92	96	92	89	92	89	86	88	86	84	81
2	97	88	81	75	94	86	79	74	83	77	72	79	74	70	76	72	68	66
3	88	76	67	60	85	75	66	60	71	64	59	68	63	58	66	61	56	54
4	79	66	57	50	77	65	56	49	62	55	49	60	53	48	58	52	47	45
5	72	58	49	42	70	57	48	41	55	47	41	53	46	40	51	45	40	37
6	66	52	42	35	64	51	42	35	49	41	35	47	40	34	45	39	34	32
7	61	46	37	30	59	45	36	30	44	36	30	42	35	29	41	34	29	27
8	56	41	32	26	54	41	32	26	39	31	26	38	31	26	37	30	25	23
9	52	38	29	23	50	37	28	23	36	28	23	34	27	22	33	27	22	20
10	48	34	26	20	47	34	26	20	33	25	20	31	25	20	31	24	20	18

LAMPS (number of lamps)

LUMINAIRE BUDGETARY DIAGRAM



ZONAL LUMEN SUMMARY

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
5.06 lm	18.2 lm	41.1 lm	69.0 lm	88.1 lm	80.4 lm	53.8 lm	26.0 lm	9.30 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
2.32 lm	0.358 lm	0.130 lm	0.072 lm	0.046 lm	0.024 lm	0.010 lm	0.005 lm	0.002 lm

Flicker /TLA details

FLICKER

Flicker Meter Type Viso Systems LabFlicker
 Frequency of input power 50 Hz
 Flicker/TLA sample rate 20000 samples/s

Measurement time
 PstLM 180 sec
 All other indices 1,2 sec

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency 99.01 Hz
 Percent Flicker 0.11 %
 Flicker index 0

Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz 0.05 %
 JA8/10 90 Hz 0.05 %
 JA8/10 200 Hz 0.07 %
 JA8/10 400 Hz 0.07 %
 JA8/10 1000 Hz 0.1 %


TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value ($F < 80$ Hz) 0.1
 SVM value ($80 < F < 2000$ Hz) 0


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp 0.02

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

