

astro

PHOTOMETRIC
TEST REPORT

Photometric Test Report

Report Number: POTS/GJ13090	Report Date: 06-03-2013	Prepared By: G John
Test Laboratory: Photometric and Optical Testing Services, Cotswold Business Centre, 42 A P Ellis Road, Rissington Business Park, Upper Rissington, Gloucestershire, GL54 2QB		
Company Registration Number: Registered in England & Wales No. OC352911		
Registered Address: Thistle Down Barn, Holcot Lane, Sywell, Northampton, NN6 0BG		

Client Details

Company: Astro Lighting	Email: technical@astrolighting.co.uk
Address: Astro Lighting Limited, G2 River Way, Harlow CM20 2DP, Great Britain	

Details of Product Tested

Manufacturer: Astro Lighting	Source Type: Domestic light
Model: TEETOO 550 12V	Serial Number: 1161010
Lamp Type: 10 W G4	
Power Supply Used: Uninterruptible AC power supply	
Voltage(AC V) = 241.6	Current (mA)= 200
Power (Watts)= 47.75	Power factor= 0.9896

Integrating Sphere Test

Date of Test: 13-02-2013	Ambient Temperature: 25°C
Measurement Filename: TEETOO 550 12V	
Instrument Used: Labsphere model CSLMS HALOGEN 4060 integrating sphere spectroradiometer	
Integrating Sphere Size: 1m	Measurement Geometry ($2\pi / 4\pi$): 4π
Sample Orientation: Horizontal	Auxiliary Correction Applied: YES
Comments:	
Date of Last Calibration (Operating Hours): 08-11-2012 (02:36)	Spectral Flux Standard Lamp Used: SCL-1400
Standard Lamp Serial Number: K75	Traceable: to NIST standards
Calibration Certificate Number: DM-02008-001	Calibration Certificate Date: 19 th February 2010
Calibration Lamp Uncertainty: $\pm 0.67\% (k=2)$	
Results	
Flux (lumens): 204.6	Rated lamp flux (lumens): 100*4
CIE 1931 Chromaticity Cx: 0.4547	CIE 1931 Chromaticity Cy: 0.4100
CRI (%): 99.8	CCT (K): 2766
LOR (%): 51.0	




Figure 1: Spectral Irradiance




Figure 2: CIE 1931 diagram.

Goniophotometer Test				
Date of Test: 13-02-2013	Ambient Temperature: 25°C			
Measurement Filename: TEETOO 550 12V				
Instrument Used: Radiant Imaging NFMS0800 Goniometer with ProMetric PM-1200N-1 Imaging Photometer				
Photometer Working Distance: 1.5 m	Measurement Geometry: Near-Field			
Comments:				
Reference Photometer Used: Specbos1201	Reference Photometer Serial Number: 2911670			
Traceable: to NPL standards, UKAS Accredited	Calibration Certificate Number: 121104			
Calibration Certificate Date: 25 th October 2011	Sample Stabilisation Time (minutes): 24			
Reference Photometer Calibration Uncertainty: ± 2.4% (k=2, 20-200 lux, CIE illuminant A source)				
Scan Set Up				
Direction	Range	Increment		
Inclination Zone 1	0-180°	3°		
Azimuth	0-360°	10°		
Results				
Integrated Luminous Flux (lumens): 204.6	Peak Intensity (3° Spot, candelas): 81.1	Efficacy (lumens/Watt): 4.28		
Beam Angle (50% of max intensity C0-180, degrees): 169.9				
Photometric Filename (IES LM-63-2002): TEETOO 550 12V				
IES File – Absolute or Relative Format? Relative				
Photometric Filename (EULUMDAT): TEETOO 550 12V				
EULUMDAT File – Absolute or Relative Format? Relative				




Figure 3: Far-Field Luminous Intensity (C0-180, Cartesian Coordinates)




Figure 4: Far-Field Luminous Intensity (C0-180, C90-270, Polar Coordinates)




Figure 4. Illuminance cone diagram.

Reflectance of												
Ceiling	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
Floor Cavity	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimension												
x	y		Viewed crosswise					Viewed endwise				
2H	2H	15.0	16.8	15.4	17.2	17.6	18.8	20.6	19.2	21.0	21.4	
	3H	18.1	19.8	18.5	20.2	20.7	22.6	24.3	23.0	24.7	25.1	
	4H	20.1	21.8	20.6	22.2	22.6	24.1	25.7	24.5	26.1	26.6	
	6H	22.0	23.6	22.5	24.0	24.5	24.2	25.8	24.7	26.2	26.7	
	8H	23.0	24.5	23.4	24.9	25.4	24.2	25.7	24.6	26.1	26.6	
	12H	23.8	25.2	24.2	25.7	26.2	24.1	25.6	24.6	26.0	26.5	
4H	2H	17.1	18.7	17.5	19.1	19.6	20.2	21.8	20.6	22.2	22.7	
	3H	20.1	21.5	20.5	22.0	22.4	24.1	25.6	24.6	26.0	26.5	
	4H	21.9	23.2	22.4	23.7	24.2	25.9	27.3	26.4	27.7	28.2	
	6H	23.9	25.1	24.4	25.6	26.1	26.4	27.6	26.9	28.1	28.6	
	8H	25.2	26.3	25.7	26.8	27.4	26.4	27.5	26.9	28.0	28.6	
	12H	26.6	27.7	27.1	28.1	28.7	26.4	27.5	26.9	27.9	28.5	
8H	4H	23.4	24.5	23.9	25.0	25.6	26.8	27.9	27.3	28.4	28.9	
	6H	25.5	26.5	26.0	27.0	27.5	27.6	28.6	28.1	29.1	29.7	
	8H	26.8	27.7	27.3	28.2	28.8	27.9	28.8	28.5	29.3	29.9	
	12H	28.3	29.1	28.9	29.7	30.2	28.1	28.9	28.7	29.5	30.0	
12H	4H	23.7	24.8	24.2	25.2	25.8	27.0	28.0	27.5	28.5	29.1	
	6H	26.0	26.9	26.6	27.4	28.0	28.0	28.9	28.6	29.5	30.0	
	8H	27.4	28.2	27.9	28.7	29.3	28.4	29.2	29.0	29.8	30.3	

Table 1. UGR values

	0	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180
0	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7
3	13.0	13.6	14.2	14.7	14.9	15.4	15.7	15.7	15.5	15.2	14.9	14.5	14.2	13.9	13.6	13.5	13.3	13.1	12.8
6	14.4	15.5	16.5	16.5	16.2	16.9	17.3	17.7	19.1	19.8	19.4	18.7	18.1	17.2	16.6	15.7	15.0	14.7	13.6
9	17.3	18.6	20.1	20.1	19.2	20.1	21.3	21.5	22.4	22.3	21.5	20.1	18.1	16.9	15.8	14.9	14.0	15.8	14.9
12	19.7	19.0	20.8	21.4	22.3	22.2	23.1	23.2	23.1	23.1	22.2	20.9	18.1	16.9	15.2	14.6	12.5	12.5	13.8
15	21.2	20.2	21.7	22.1	23.2	22.1	23.5	24.1	23.7	23.4	22.0	20.0	16.9	15.4	13.3	10.8	8.8	8.3	11.8
18	22.0	20.9	22.6	22.4	23.2	22.8	23.9	23.2	23.6	23.4	20.5	18.5	16.9	13.2	9.3	5.6	4.7	6.6	12.0
21	23.1	21.9	22.3	22.6	22.4	23.4	23.4	23.9	23.8	23.6	21.3	17.2	15.1	11.0	4.7	3.2	4.1	5.9	12.1
24	22.9	21.6	22.7	22.8	22.6	23.4	24.9	23.6	24.6	23.1	20.9	17.5	12.9	7.4	2.9	2.7	3.9	5.7	13.4
27	23.4	22.7	22.4	23.2	22.8	22.8	24.1	24.9	24.9	23.9	20.1	16.0	12.1	4.0	3.1	2.6	3.9	5.5	14.3
30	23.5	21.8	23.1	23.2	22.9	24.0	25.2	24.9	25.2	24.7	20.6	14.7	10.4	4.0	3.5	2.6	3.8	6.0	15.4
33	22.6	22.3	22.0	22.6	22.7	24.3	25.9	25.0	26.4	25.3	19.1	16.6	6.5	4.6	3.6	2.9	3.7	5.8	16.0
36	23.9	21.9	22.2	22.6	23.5	24.3	25.5	24.5	25.1	25.2	17.7	14.0	6.9	4.8	4.3	3.0	3.4	6.0	15.7
39	24.0	21.4	22.8	22.4	23.7	24.5	25.1	24.4	24.4	21.9	17.7	9.8	6.8	5.1	4.3	3.5	3.2	5.2	16.5
42	24.4	21.9	22.2	22.3	23.7	24.3	23.7	23.1	22.3	19.5	16.6	8.5	3.8	4.7	4.6	3.8	3.2	4.7	15.4
45	23.7	22.0	22.6	23.4	23.8	23.8	22.1	20.6	20.2	19.3	13.8	9.3	2.1	3.8	4.1	4.4	3.3	4.3	15.1
48	24.6	21.3	21.9	23.2	24.0	22.6	20.0	20.5	20.2	18.6	13.9	7.7	1.9	2.3	2.9	4.5	3.4	5.0	14.9
51	23.6	21.4	22.3	23.4	23.1	20.3	20.7	19.7	20.2	18.2	12.6	5.8	1.4	0.8	2.3	4.1	3.6	5.0	14.9
54	24.0	21.8	21.9	22.8	20.8	20.3	20.6	20.0	19.6	18.1	11.4	3.4	1.0	0.6	1.1	2.7	3.9	4.6	13.2
57	25.4	21.1	21.6	21.8	20.8	19.7	19.7	20.0	20.6	17.7	11.1	2.1	0.5	0.5	0.8	1.9	4.5	4.5	13.6
60	24.3	20.9	20.0	21.4	19.6	20.4	20.4	20.4	19.6	17.5	11.3	2.0	0.4	0.3	0.6	1.1	4.8	4.5	13.9
63	26.5	21.1	21.2	20.4	19.7	20.0	20.6	20.2	20.6	17.5	12.4	2.7	0.5	0.4	0.6	0.8	4.2	4.5	14.4
66	24.2	21.3	20.8	19.5	19.9	19.7	20.0	20.1	20.4	17.0	12.0	3.1	0.5	0.5	0.5	0.6	2.1	4.8	14.8
69	25.5	20.6	20.8	19.1	19.6	19.9	19.9	20.7	21.3	16.9	10.2	2.7	0.3	0.5	0.4	0.5	1.0	4.2	13.5
72	28.6	20.3	19.9	19.1	20.0	19.1	19.9	20.0	20.3	17.1	7.9	1.6	0.6	0.5	0.0	0.4	0.5	2.3	5.6
75	26.0	19.3	19.8	19.4	19.4	19.1	19.9	19.5	19.8	17.1	4.4	0.6	0.4	0.4	0.4	0.4	0.5	0.6	2.9
78	25.0	18.8	19.7	19.0	19.3	20.0	20.1	20.4	20.1	17.5	3.7	0.4	0.4	0.4	0.5	0.5	0.6	0.4	2.5
81	23.7	18.1	18.8	18.8	19.4	19.8	20.0	20.6	20.7	17.6	3.8	0.6	0.5	0.5	0.6	0.0	0.5	0.4	2.4
84	21.2	17.9	19.2	19.1	20.1	20.2	20.3	20.2	20.2	17.5	3.9	0.0	0.8	0.5	0.5	0.4	0.5	0.4	2.6
87	16.2	16.3	16.8	16.7	17.9	18.2	17.8	17.8	18.8	16.1	3.5	0.0	0.4	0.0	0.5	0.6	0.6	0.0	1.9
90	12.1	11.4	13.5	12.7	14.0	14.2	13.6	13.6	15.1	12.4	2.3	0.0	1.2	0.4	0.5	0.0	0.4	0.4	1.1
93	4.1	3.7	3.5	3.3	3.0	2.8	2.5	2.3	1.9	1.5	1.2	1.1	0.9	0.8	0.7	0.6	0.4	0.3	0.5

96	1.9	1.8	1.7	1.4	1.4	1.3	1.1	1.0	0.9	0.8	0.4	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.3
99	0.7	0.6	0.5	0.4	0.4	0.3	0.3	0.2	0.3	0.3	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.2	0.2
102	0.3	0.3	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
105	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
108	0.2	0.2	0.2	0.2	0.1	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
111	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
114	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
117	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
120	0.2	0.2	0.2	0.2	0.1	0.1	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
123	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
126	0.1	0.1	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
129	0.1	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
132	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
135	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
138	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
141	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
144	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
147	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
150	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
153	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
156	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
159	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
162	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
165	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
168	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
171	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
174	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1
177	0.1	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0.1
180	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

Table 2a. Luminous intensity values, azimuth 0-180°

	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350
0	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7	12.7
3	12.6	12.6	12.9	13.3	13.8	14.0	14.1	14.1	14.0	14.0	13.8	13.7	13.5	13.2	12.9	12.6	12.7
6	13.2	13.8	14.6	15.6	16.7	17.3	18.1	18.4	18.3	18.8	18.7	17.6	16.8	16.2	15.1	13.9	14.0
9	13.4	15.0	16.9	20.2	22.0	22.7	24.3	26.0	26.8	26.0	26.6	23.7	22.1	21.1	18.8	17.6	17.6
12	14.8	18.4	21.6	25.7	28.2	30.7	36.0	36.7	36.9	37.2	35.4	33.9	28.7	26.8	23.0	20.1	19.3
15	16.2	21.8	26.9	34.1	37.5	42.3	44.2	47.4	46.1	47.3	46.6	44.3	39.7	33.7	28.0	23.5	21.6
18	17.9	26.3	33.8	41.3	47.5	50.6	52.4	52.6	55.3	52.7	55.8	54.2	51.0	44.7	36.4	27.1	23.9
21	20.8	30.4	40.7	46.9	56.7	58.6	60.6	57.7	61.3	60.0	64.0	63.6	59.9	54.3	41.6	33.7	24.8
24	23.6	34.9	48.3	54.4	64.4	65.6	65.3	63.0	64.2	67.0	69.8	72.2	66.7	62.3	52.2	34.8	27.8
27	26.4	40.2	55.2	62.3	69.0	69.1	65.8	67.5	66.1	67.9	73.2	75.3	76.3	70.2	58.4	41.6	29.4
30	29.2	43.5	60.1	67.5	69.8	69.2	66.0	61.3	60.6	64.0	71.1	78.0	77.0	75.0	66.1	46.0	30.7
33	32.4	45.3	64.6	69.4	67.7	66.2	60.2	52.1	51.9	56.5	64.5	70.2	79.6	78.3	66.2	52.7	33.5
36	34.2	48.2	68.5	71.1	67.1	59.7	53.2	44.0	43.9	49.8	56.9	62.5	72.9	81.1	74.3	54.9	34.1
39	35.0	49.5	69.9	72.6	64.1	51.6	47.9	40.0	39.9	46.2	54.4	61.2	65.3	75.2	76.5	67.3	35.7
42	33.9	50.0	71.8	71.9	61.5	49.8	45.7	41.8	39.4	47.3	53.1	59.2	63.4	72.1	75.4	59.4	36.4
45	34.9	52.0	70.6	69.5	57.1	50.5	46.7	43.7	43.3	49.6	53.8	58.8	60.2	64.9	74.7	66.9	38.7
48	37.0	54.6	71.1	64.9	55.3	52.3	49.9	48.0	47.9	53.2	56.5	62.8	62.1	61.9	64.7	64.5	40.1
51	37.9	57.6	71.9	60.0	55.9	53.2	52.0	51.6	52.4	56.3	61.0	63.6	63.1	58.0	56.3	66.6	42.2
54	38.8	60.8	71.2	59.7	57.1	56.3	56.8	56.3	57.2	60.4	63.4	66.4	63.7	61.3	55.3	53.6	44.4
57	40.2	60.7	67.0	58.6	59.3	61.3	60.2	60.4	59.7	63.0	65.8	68.8	67.8	62.2	56.7	47.8	42.7
60	39.0	58.9	63.2	58.6	60.8	63.6	63.3	64.3	63.5	65.8	69.2	71.6	71.7	66.6	50.7	42.0	46.6
63	39.2	58.1	62.1	59.8	62.2	66.5	65.2	66.6	67.0	67.9	72.8	72.3	74.6	66.6	49.6	41.0	49.7
66	39.6	58.0	59.8	61.5	65.2	69.2	67.3	67.5	68.4	71.5	75.9	76.0	75.4	66.0	54.4	39.0	46.8
69	39.8	58.2	59.3	62.8	68.0	68.9	67.2	68.1	69.0	72.5	75.9	78.6	73.6	66.3	53.9	42.1	54.0
72	39.4	55.5	58.7	65.1	69.8	69.6	69.6	67.7	69.6	69.8	76.6	77.3	73.4	67.7	51.4	40.2	58.1
75	46.1	53.7	58.1	63.1	70.2	70.8	66.0	49.1	43.7	61.2	72.1	76.8	73.3	69.5	50.2	38.7	54.5
78	18.3	52.9	58.0	61.3	56.5	52.1	42.3	12.0	8.5	27.1	55.6	61.7	70.1	69.0	50.4	38.5	52.6
81	13.3	56.0	54.7	57.8	34.8	25.8	23.8	1.7	0.7	8.0	41.8	43.4	61.3	61.6	51.5	37.9	56.0
84	32.8	55.0	48.2	46.8	24.2	18.1	14.0	1.3	0.0	4.9	38.4	38.3	47.0	47.0	46.7	37.5	59.2
87	39.4	40.2	33.7	31.3	14.2	11.0	5.3	0.6	0.0	3.0	31.3	31.4	33.7	32.8	30.3	32.5	55.4
90	23.1	22.8	20.4	20.9	9.1	7.1	3.0	0.5	0.0	2.4	24.2	24.0	25.1	24.7	21.9	25.8	38.3
93	3.3	4.5	6.1	6.9	4.9	4.2	4.6	1.0	0.4	3.9	9.8	8.4	8.9	7.7	4.9	4.5	5.0

96	1.9	3.4	4.4	5.6	4.9	4.3	4.7	1.0	0.4	3.2	6.5	5.8	6.4	5.8	4.6	3.0	1.7
99	1.3	3.0	4.0	4.5	4.2	4.1	5.1	2.7	3.3	4.7	5.7	5.3	5.3	4.9	3.9	2.4	0.7
102	0.5	2.3	3.3	3.6	3.8	4.3	6.5	6.6	7.9	8.0	6.0	4.8	3.9	3.7	2.9	1.7	0.4
105	0.3	1.6	2.5	3.1	3.7	4.7	7.2	8.0	8.6	8.0	6.2	4.6	3.5	2.6	1.8	0.9	0.3
108	0.2	0.8	1.8	2.9	3.9	5.3	7.2	7.9	8.0	7.6	6.4	4.3	3.2	2.1	1.1	0.2	0.2
111	0.2	0.2	1.4	2.6	3.9	5.6	7.1	7.5	7.7	7.2	6.4	4.2	2.9	1.7	0.7	0.2	0.2
114	0.2	0.2	1.0	2.3	3.8	5.4	6.5	6.9	7.0	6.7	5.9	4.1	2.6	1.2	0.5	0.2	0.2
117	0.2	0.2	0.6	1.9	3.5	4.8	5.6	6.1	6.3	5.9	5.2	3.9	2.3	0.9	0.5	0.2	0.2
120	0.2	0.2	0.3	1.3	2.7	3.9	4.7	5.1	5.3	5.0	4.3	3.2	1.5	0.7	0.3	0.2	0.2
123	0.2	0.2	0.2	0.8	1.5	2.9	3.6	4.2	4.4	4.0	3.3	2.2	0.8	0.4	0.2	0.2	0.2
126	0.2	0.2	0.2	0.4	0.7	2.0	2.7	3.2	3.4	3.1	2.3	1.1	0.5	0.3	0.2	0.2	0.1
129	0.2	0.1	0.1	0.2	0.3	0.9	1.7	2.0	2.2	1.7	1.1	0.3	0.3	0.2	0.1	0.1	0.1
132	0.1	0.1	0.1	0.1	0.2	0.3	0.7	0.9	0.9	0.6	0.3	0.2	0.2	0.2	0.1	0.1	0.1
135	0.1	0.1	0.1	0.1	0.2	0.2	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.1
138	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1
141	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1
144	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1
147	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1
150	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1
153	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.2	0.2	0.1	0.1	0.1
156	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1
159	0.1	0.1	0.2	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1	0.1
162	0.1	0.1	0.2	0.2	0.2	0.2	0.1	0.2	0.2	0.1	0.2	0.2	0.2	0.1	0.1	0.1	0.1
165	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1
168	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1
171	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1	0.1	0.1
174	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.1	0.1	0.2	0.2	0.2	0.1	0.1
177	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.1
180	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2

Table 2b. Luminous intensity values, azimuth 190-350°

Signature:



Print Name:

GH JOHN

Date:

06-03-2013

Partner / Director

Duly authorised to sign on behalf of:

Photometric and Optical Testing Services LLP