



PRODUCT SPECIFICATION

GENERAL

FINISH:	White	CABLE LENGTH:	Not Applicable
MAIN MATERIAL:	Metal - Mild Steel	GROSS WEIGHT:	To Be Advised
DIMENSIONS:	D: 95mm DIA: 300mm	CLASS:	CE (Class II)
INSTALLATION ORIENTATION:	Ceiling Mount	IP RATING:	IP44
CUT OUT HOLE:	Not Applicable	BATHROOM ZONE:	Zone 2, 3
RECESS DEPTH:	Not Applicable	VOLTAGE:	Mains 230V
FIRE RATING:	Not Applicable	PRODUCT F MARK:	Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:	4pin-2D	MACADAM ELIPSE:	Not Applicable
MAXIMUM WATTAGE:	28W	UGR:	Not Applicable
MAXIMUM LAMP LENGTH:	Lamp Dependent	BEAM ANGLE:	113.8 (Degrees)
LAMP INCLUDED?	Yes	TILT ADJUSTMENT ANGLE:	Not Applicable
LUMINOUS FLUX:	1110 (lm)	ROTATION ADJUSTMENT ANGLE:	Not Applicable
COLOUR TEMP:	3500 (K)	AVERAGE LIFESPAN:	8,000 (Hrs)
CRI:	To Be Advised	L70:	Not Applicable
R9:	7.9		

ELECTRICAL

SWITCHED:	No	SUPPLY FREQUENCY:	50/60 (Hz)
DIMMABLE:	No	DRIVER / BALLAST VOLTAGE:	220-240 (V)
DIMMING METHOD:	Not Applicable	DRIVER AVERAGE LIFESPAN:	Not Applicable
DRIVER OUTPUT CURRENT:	Not Applicable	EFFICACY:	37.38 (lm/W)
DRIVER OUTPUT VOLTAGE:	Not Applicable	DRIVER / BALLAST INCLUDED?	Yes (Integral)

ADDITIONAL INFORMATION



BOX QUANTITY
To Be Advised

PRODUCT ELEVATIONS

