

LED DRIVER 700MA 14W

CODE 1987 / SKU 6008032

astro



SPECIFICATION

TYPE	Constant current
DRIVER CURRENT	700mA
DRIVER VOLTAGE	N/A
DIMMABLE	LEADING/ TRAILING EDGE
ELECTRICAL CLASS	CLASS 2
SUPPLY VOLTAGE	220-240V AC
SUPPLY FREQUENCY	50/60Hz
POWER FACTOR	0.95
MIN. OUTPUT VOLTAGE	10.0V DC
MAX. OUTPUT VOLTAGE	20.0V DC
MIN. OUTPUT POWER	7.0W
MAX. OUTPUT POWER	14.0W
INRUSH CURRENT	1.7A 40 μ S
IP RATING	IP20
WORKING TEMPERATURE	-25°C - +50°C
CONNECTION TYPE	Screw terminals
LENGTH	101.5mm
WIDTH	51mm
HEIGHT	29.5mm
MIN. CIRCULAR APERTURE	59mm/2-5/16"
MAX. LED DISTANCE	2m
MANUFACTURER	TRIDONIC
MODEL NUMBER	LCBI 14W 700MA BASIC SR ADV

Wire LED products in series.

To calculate product compatibility, visit the driver calculator on each product page on the Astro website.

See the Astro website for installation guides.