OSCA TWIN 140 ADJUSTABLE **5684 SKU** 1252005

astro

Not Applicable

2.50 (Kg)



PRODUCT SPECIFICATION

GENERAL

FINISH: Plaster CABLE LENGTH:

MAIN MATERIAL: Plaster GROSS WEIGHT:

DIMENSIONS: H:140mm W:220mm D:110mm CLASS:

Lamp Dependant

 DIMENSIONS:
 H:140mm W:220mm D:110mm
 CLASS:
 CE (Class I)

 INSTALLATION ORIENTATION:
 Ceiling Mount
 IP RATING:
 IP20

CUT OUT HOLE: Not Applicable BATHROOM ZONE: Zone 3

RECESS DEPTH: VOLTAGE: Mains 230 (V)

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:LED GU10MACADAM ELLIPSE:Not ApplicableMAXIMUM WATTAGE:2 x 6W MaxUGR:Not ApplicableMAXIMUM LAMP LENGTH:55 (mm)BEAM ANGLE:Lamp Dependant

LAMP INCLUDED? TILT ADJUSTMENT ANGLE: No 30 (Degrees) **LUMINOUS FLUX:** Lamp Dependant ROTATION ADJUSTMENT ANGLE: 330 (Degrees) COLOUR TEMP: AVERAGE LIFESPAN: Lamp Dependant Lamp Dependant CRI: Lamp Dependant L70: Not Applicable

ELECTRICAL

R9:

SWITCHED:NoSUPPLY FREQUENCY:Not ApplicableDIMMABLE:YesDRIVER/BALLAST VOLTAGE:Not ApplicableDIMMING METHOD:Lamp DependantDRIVER AVERAGE LIFESPAN:Not Applicable

DRIVER OUTPUT CURRENT: Not Applicable EFFICACY: Lamp Dependant
DRIVER OUTPUT VOLTAGE: Not Applicable DRIVER/BALLAST INCLUDED? Not Applicable

ADDITIONAL INFORMATION

BOX G

BOX QUANTITY x 6

CE







