

# LED Halo Glass GU10

## Halo Elite Glass 4.2W LED Dimmable GU10 - 4000K

### Part Code: 60644

The Halo Elite Glass combines the retro feel of halogen lamps with the efficiency of LED technology. The high-grade driver within the Halo Elite Glass allows for smooth dimming at minimum and maximum load levels. The precision moulded polycarbonate lens ensures precise beam angle light distribution.

- True fit GU10 size
- Dimmable & Non Dim available
- Suitable for fire rated and IP rated fixtures
- Compatible with most branded Trailing Edge Dimmers, including the BELL Smart Universal LED Trailing/Leading Edge Dimmer Module Code: 10803
- Precision moulded polycarbonate lens



**Aesthetically**  
Pleasing



**3 Year**  
Guarantee



**80**  
Colour Rendering Index



**240**  
Volts



# LED Halo Glass GU10



|                          |               |
|--------------------------|---------------|
| <b>Product Category</b>  | Lamps / LED   |
| <b>Application</b>       | LED GU10 Lamp |
| <b>Product Warranty</b>  | 3 Years       |
| <b>EAN</b>               | 5013588606446 |
| <b>Commodity Code</b>    | 8539520000    |
| <b>Country of Origin</b> | CN            |

## Technical Specification

|                                |        |
|--------------------------------|--------|
| Wattage (W)                    | 4.2    |
| Equivalent Wattage (W)         | 75     |
| Volts (V)                      | 240    |
| Colour Temperature (K)         | 4000   |
| Lumen Output (lm)              | 470    |
| Lumens per Watt (lm/W)         | 112    |
| Candelas                       | 870    |
| CRI (ra)                       | 80     |
| Frequency (Hz)                 | 50     |
| LED Drive Current              | 13.4mA |
| Energy Consumption (kWh/1000h) | 5      |
| Life Hours                     | 25000  |
| Energy Rating                  | E      |
| Lumen Maintenance Ratio        | 80     |

## Packaging Information

|                                |               |
|--------------------------------|---------------|
| Minimum Order Quantity         | 10            |
| Height (mm)                    | 53            |
| Diameter (mm)                  | 50            |
| Individual Product Weight (kg) | 0.047         |
| Single Box Weight (kg)         | 0.064         |
| Single Box Height (mm)         | 60            |
| Single Box Width (mm)          | 52            |
| Single Box Depth (mm)          | 52            |
| Single Box Volume              | 0.00016       |
| Inner Box Qty                  | 10            |
| Inner Box Barcode              | 6064400000010 |
| Inner Box Weight (kg)          | 0.695         |
| Inner Box Height (mm)          | 75            |
| Inner Box Width (mm)           | 112           |
| Inner Box Depth (mm)           | 274           |
| Inner Box Volume               | 0.0023        |
| Outer Box Qty                  | 100           |
| Outer Box Barcode              | 6064400000100 |
| Outer Box Weight (kg)          | 7.44          |
| Outer Box Height (mm)          | 177           |
| Outer Box Width (mm)           | 289           |
| Outer Box Depth (mm)           | 577           |
| Outer Box Volume               | 0.02952       |
| UNSPSC Code                    | 39101628      |

# LED Halo

## Glass GU10

| Additional Information |      |
|------------------------|------|
| Beam Angle             | 38°  |
| Cap                    | GU10 |